


LED BAW



Aluminum die-cast body and powder coating or oil painting finishing;
By using the third generation of CITIZEN COB LED chip; good lighting effect, no lighting spot; unique thermal ventilation system to create extreme low heat and offers an excellent lumen performance; available with different interchangeable beam angles.
With clip adjustment to have an easier installation.

Suitable for use in areas like hotels, villas, shopping malls and etc.
This product is in compliance with CE and RoHS directives.



CE IP20
 NW: 0.93Kg
 0° ~ 30° Tilt
 171

 350° Horizontally
 5 ~ 15mm
 150mm




R3B0367 AW
R3B0367 AS

15W LED 2700K-3000K / excl. 360mA LED Driver / 37V
15W LED 2700K-3000K / excl. 360mA LED Driver / 37V



High	illuminance	Diameter
1 m	9059 lx	0.17 m
2 m	2265 lx	0.35 m
3 m	1007 lx	0.50 m
4 m	566 lx	0.67 m
5 m	362 lx	0.85 m



AW
AS

15W LED 2700K-3000K / excl. 360mA LED Driver / 37V
15W LED 2700K-3000K / excl. 360mA LED Driver / 37V



High	illuminance	Diameter
1 m	2771 lx	0.42 m
2 m	693 lx	0.86 m
3 m	308 lx	1.30 m
4 m	173 lx	1.72 m
5 m	111 lx	2.15 m



AW
AS

15W LED 2700K-3000K / excl. 360mA LED Driver / 37V
15W LED 2700K-3000K / excl. 360mA LED Driver / 37V



High	illuminance	Diameter
1 m	1780 lx	0.65 m
2 m	445 lx	1.30 m
3 m	198 lx	1.95 m
4 m	111 lx	2.60 m
5 m	71 lx	3.25 m



AW
AS

15W LED 2700K-3000K / excl. 360mA LED Driver / 37V
15W LED 2700K-3000K / excl. 360mA LED Driver / 37V



High	illuminance	Diameter
1 m	647 lx	1.15 m
2 m	162 lx	2.31 m
3 m	72 lx	3.46 m
4 m	40 lx	4.62 m
5 m	26 lx	5.77 m



OSRAM LED Driver
Pout: 15W
Uout: 27 ~ 54VDC
Un: 100 ~ 240VAC
Iout: 290 ~ 420mA
ADO164



TCI LED Driver
Pout: 15W
Uout: 43VDC
Un: 100 ~ 240VAC
Iout: 350mA
ADO104