


LED BAW



Aluminum die-cast body and powder coating or oil painting finishing; By using the third generation of CITIZEN COB LED chip; good lighting effect, no lighting spot; unique thermal ventilation system to create extreme low heat and offers an excellent lumen performance; available with different interchangeable beam angles. With clip adjustment to have an easier installation.

Suitable for use in areas like hotels, villas, shopping malls and etc. This product is in compliance with CE and RoHS directives



GW: 13.2Kg

NW: 0.85Kg
   
  
 156
   
 160
   
 5 ~ 15mm
   
 P 150mm



COB LED(CITIZEN)

**R3B0371** AW


20W LED 2700K-3000K / excl. 500mA LED Driver / 37V

**R3B0371** AS

20W LED 2700K-3000K / excl. 500mA LED Driver / 37V



High	illuminance	Diameter
1 m	14766 lx	0.17 m
2 m	3692 lx	0.35 m
3 m	1461 lx	0.50 m
4 m	923 lx	0.67 m
5 m	591 lx	0.85 m



AW

20W LED 2700K-3000K / excl. 500mA LED Driver / 37V

AS

20W LED 2700K-3000K / excl. 500mA LED Driver / 37V



High	illuminance	Diameter
1 m	5076 lx	0.42 m
2 m	1269 lx	0.86 m
3 m	564 lx	1.30 m
4 m	317 lx	1.72 m
5 m	203 lx	2.15 m



AW

20W LED 2700K-3000K / excl. 500mA LED Driver / 37V

AS

20W LED 2700K-3000K / excl. 500mA LED Driver / 37V



High	illuminance	Diameter
1 m	2546 lx	0.57 m
2 m	637 lx	1.15 m
3 m	283 lx	1.96 m
4 m	159 lx	2.47 m
5 m	102 lx	3.16 m



AW

20W LED 2700K-3000K / excl. 500mA LED Driver / 37V

AS

20W LED 2700K-3000K / excl. 500mA LED Driver / 37V



High	illuminance	Diameter
1 m	1028 lx	1.15 m
2 m	257 lx	2.31 m
3 m	114 lx	3.46 m
4 m	64 lx	4.82 m
5 m	41 lx	5.77 m



**OSRAM** LED Driver  
 Pout: 30W  
 Uout: 27 ~ 54VDC  
 Un: 220 ~ 240VAC  
 Iout: 500 ~ 700mA  
**AD0165**



**TCI** LED Driver  
 Pout: 20W  
 Uout: 45VDC  
 Un: 110 ~ 240VAC  
 Iout: 500mA  
**AD0101**