



LED Lobby



**CE IP20**  
 NW: 0.52Kg  
  
 ±5 ~ 25mm  
 P 98mm



**R3B0201** AW  
**R3B0201** AS

This product contains an aluminum die-cast front and heat sink, completing with powder coating or oil painting finishing; By using the new generation of CITIZEN COB LED chip, this product creates extreme low heat and offers an excellent lumen performance; This product completes with high light transmittance PC lens, available with several different beam angles.

Suitable for use in areas like hotel, supermarket, fancy store, home and etc. This product is in compliance with CE and RoHS directives.

AW 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V  
AS 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V

High	illumination	Diameter
1 m	4976 lx	0.26 m
2 m	1244 lx	0.53 m
3 m	553 lx	0.79 m
4 m	311 lx	1.05 m
5 m	199 lx	1.32 m



AW 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V  
AS 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V

High	illumination	Diameter
1 m	2377 lx	0.46 m
2 m	594 lx	0.92 m
3 m	264 lx	1.39 m
4 m	149 lx	1.85 m
5 m	95 lx	2.31 m



AW 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V  
AS 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V

High	illumination	Diameter
1 m	1215 lx	0.65 m
2 m	304 lx	1.30 m
3 m	135 lx	1.95 m
4 m	76 lx	2.60 m
5 m	49 lx	3.25 m



AW 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V  
AS 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V

High	illumination	Diameter
1 m	662 lx	1.15 m
2 m	166 lx	2.31 m
3 m	74 lx	3.46 m
4 m	41 lx	4.62 m
5 m	26 lx	5.77 m



**OSRAM** LED Driver  
Pout: 10W  
Uout: 27 ~ 54VDC  
Un: 220 ~ 240VAC  
Iout: 290 / 350 / 420mA  
**AD0164**



**TCI** LED Driver  
Pout: 10W  
Uout: 43VDC  
Un: 100 ~ 240VAC  
Iout: 250mA  
**AD0106**