


Deep



GW: 7.92Kg

NW: 0.13Kg

128
 ∅90
 ±0.5 ~ 25mm
 P 83mm



QPAR16(PHILIPS)

R4A0028 AW

Max.50W / GU10 / 230V~50Hz

R4A0028 AS

Max.50W / GU10 / 230V~50Hz



	1 m	592 lx	0.65 m
60°	2 m	148 lx	1.30 m
	3 m	66 lx	1.95 m
30°	4 m	37 lx	2.60 m
	5 m	24 lx	3.25 m
		High	illuminance Diameter



LED QPAR16(PHILIPS)

7W / 25° / 2700K / 1050cd / CRI: 80 / 40000hrs / GU10

7W / 40° / 2700K / 450cd / CRI: 80 / 40000hrs / GU10

7W / 25° / 3000K / 1200cd / CRI: 80 / 40000hrs / GU10

7W / 40° / 3000K / 500cd / CRI: 80 / 40000hrs / GU10

7W / 25° / 4000K / 1200cd / CRI: 80 / 40000hrs / GU10

7W / 40° / 4000K / 500cd / CRI: 80 / 40000hrs / GU10



	1 m	1038 lx	0.46 m
60°	2 m	260 lx	0.92 m
	3 m	115 lx	1.39 m
30°	4 m	65 lx	1.85 m
	5 m	42 lx	2.31 m
		High	illuminance Diameter



	1 m	447 lx	0.73 m
60°	2 m	112 lx	1.46 m
	3 m	50 lx	2.18 m
30°	4 m	28 lx	2.91 m
	5 m	18 lx	3.64 m
		High	illuminance Diameter

