


Trim



GW: 8.28Kg

CE IP20
 NW: 1.57Kg

 +30° ~ -30° Tilt
 169 x 165mm



COB LED(CITIZEN)

This product contains an aluminum die-cast front and heat sink, completes with powder coating or oil painting finishing;
 By using the new generation of CITIZEN COB LED chip, this product creates extreme low heat and offers an excellent lumen performance;
 This product completes with high light transmittance PC lens, available with several different beam angles.
 This product is with springs for recessed mounting.

It is suitable for hotels, department stores, various franchise stores, garment stores, superfine goods stores, art galleries, entertainment places, homes, etc.;
 This product is CE certified and all materials are in conformity with RoHS standard.

R3B0339 AW

20W LED 2700K-3000K / excl. 480mA LED Driver / 37V

R3B0339 AS

20W LED 2700K-3000K / excl. 480mA LED Driver / 37V



High	1 m	2 m	3 m	4 m	5 m	14900cd
60°	14766 lx	3692 lx	1461 lx	923 lx	591 lx	0.17 m
30°						0.35 m
						0.50 m
						0.67 m
						0.85 m



AW

20W LED 2700K-3000K / excl. 480mA LED Driver / 37V

AS

20W LED 2700K-3000K / excl. 480mA LED Driver / 37V



High	1 m	2 m	3 m	4 m	5 m	5100cd
60°	5076 lx	1269 lx	564 lx	317 lx	203 lx	0.42 m
30°						0.86 m
						1.30 m
						1.72 m
						2.15 m



AW

20W LED 2700K-3000K / excl. 480mA LED Driver / 37V

AS

20W LED 2700K-3000K / excl. 480mA LED Driver / 37V



High	1 m	2 m	3 m	4 m	5 m	2600cd
60°	2546 lx	637 lx	283 lx	159 lx	102 lx	0.57 m
30°						1.15 m
						1.95 m
						2.47 m
						3.16 m



AW

20W LED 2700K-3000K / excl. 480mA LED Driver / 37V

AS

20W LED 2700K-3000K / excl. 480mA LED Driver / 37V



High	1 m	2 m	3 m	4 m	5 m	1040cd
60°	1028 lx	257 lx	114 lx	64 lx	41 lx	1.15 m
30°						2.31 m
						3.46 m
						4.62 m
						5.77 m



OSRAM LED Driver
 Pout: 20W
 Uout: 27 ~ 54VDC
 Uin: 220 ~ 240VAC
 Iout: 500 / 600 / 700mA
AD0165



TCI LED Driver
 Pout: 20W
 Uout: 45VDC
 Uin: 110 ~ 240VAC
 Iout: 500mA
AD0101