



Recessed down lights - Trim

Trim



NW: 0.37Kg

89 30
 118 118
 +30° ~ -30° Tilt
 5 ~ 25mm
 106 x 106mm



R4B0001 AW

Max.50W / excl. Electronic Transformer / GU5.3 / AC12V

R4B0001 AS

Max.50W / excl. Electronic Transformer / GU5.3 / AC12V



High	1m	2m	3m	4m	5m
19000cd	13086 lx	3272 lx	1457 lx	818 lx	523 lx
	0.17 m	0.35 m	0.52 m	0.70 m	0.87 m
	Illuminance		Diameter		



High	1m	2m	3m	4m	5m
4400cd	4389 lx	1097 lx	488 lx	275 lx	176 lx
	0.43 m	0.85 m	1.23 m	1.55 m	1.89 m
	Illuminance		Diameter		



High	1m	2m	3m	4m	5m
2200cd	2199 lx	550 lx	244 lx	137 lx	88 lx
	0.65 m	1.30 m	2.02 m	2.57 m	3.31 m
	Illuminance		Diameter		



7W / 24° / 2700K / 1450cd / CRI: 80 / 40000hrs / GU5.3

7W / 36° / 2700K / 763cd / CRI: 80 / 40000hrs / GU5.3

7W / 60° / 2700K / 320cd / CRI: 80 / 40000hrs / GU5.3

7W / 24° / 3000K / 1550cd / CRI: 80 / 40000hrs / GU5.3

7W / 36° / 3000K / 810cd / CRI: 80 / 40000hrs / GU5.3

7W / 60° / 3000K / 341cd / CRI: 80 / 40000hrs / GU5.3

7W / 24° / 4000K / 1640cd / CRI: 80 / 40000hrs / GU5.3

7W / 36° / 4000K / 810cd / CRI: 80 / 40000hrs / GU5.3

7W / 60° / 4000K / 360cd / CRI: 80 / 40000hrs / GU5.3



High	1m	2m	3m	4m	5m
1950cd	1531 lx	383 lx	170 lx	96 lx	61 lx
	0.42 m	0.86 m	1.30 m	1.72 m	2.15 m
	Illuminance		Diameter		

