


Stores



This product contains an aluminum die-cast front and a pure aluminum heat sink, completes with powder coating finishing; By using the new generation of SHARP COB LED chip, this product creates extreme low heat and offers an excellent lumen performance; highpurity aluminum spinning, surface anodized mirror effect reflectors are available with different beam angles, all completing with high reflecting vacuum plated finishing; Clip installation and adjustable;

Suitable for use in areas like , hotel , fancy stores, supermarket and etc. This product is in compliance with CE and RoHS directives.

CE IP20
 NW: 1.91Kg

 +30° ~ -30° Tilt
 5 ~ 25mm
 310 x 154mm



COB LED(SHARP)

R3B0198 AW

2 x 30W LED 2700K-3000K / excl. 700mA LED Driver / 37V

R3B0198 AS

2 x 30W LED 2700K-3000K / excl. 700mA LED Driver / 37V



Height	Beam Angle	Illuminance (lx)	Diameter (m)
1 m	60° / 30°	11402 lx	0,26 m
2 m		2851 lx	0,53 m
3 m		1267 lx	0,79 m
4 m		713 lx	1,05 m
5 m		456 lx	1,32 m



AW

2 x 30W LED 2700K-3000K / excl. 700mA LED Driver / 37V

AS

2 x 30W LED 2700K-3000K / excl. 700mA LED Driver / 37V



AW

2 x 30W LED 2700K-3000K / excl. 700mA LED Driver / 37V

AS

2 x 30W LED 2700K-3000K / excl. 700mA LED Driver / 37V



AW

2 x 30W LED 2700K-3000K / excl. 700mA LED Driver / 37V

AS

2 x 30W LED 2700K-3000K / excl. 700mA LED Driver / 37V



Height	Beam Angle	Illuminance (lx)	Diameter (m)
1 m	60° / 30°	3097 lx	0,57 m
2 m		774 lx	1,15 m
3 m		344 lx	1,95 m
4 m		194 lx	2,47 m
5 m		124 lx	3,16 m



OSRAM LED Driver
 Pout: 30W
 Uout: 27 ~ 54VDC
 Un: 220 ~ 240VAC
 Iout: 500 / 600 / 700mA

AD0165



TCI LED Driver
 Pout: 30W
 Uout: 46VDC
 Un: 110 ~ 240VAC
 Iout: 700mA

AD0102