



LED BAW



Aluminum die-cast body and powder coating or oil painting finishing; By using the third generation of CITIZEN COB LED chip; good lighting effect, no lighting spot; available with different interchangeable beam angles.

Suitable for use in areas like hotels, villas, shopping malls and etc. This product is in compliance with CE and RoHS directives.



CE IP20
 NW: 0.40Kg
 111

 ∅ 110
 5 ~ 25mm
 100mm



R3B0365 AW
R3B0365 AS

10W LED 2700K-3000K / excl. 300mA LED Driver / 37V
10W LED 2700K-3000K / excl. 300mA LED Driver / 37V



High	1 m	2 m	3 m	4 m	5 m	illuminance	Diameter
60°	4976 lx	1244 lx	553 lx	311 lx	199 lx	0.26 m	0.53 m
30°						0.79 m	1.05 m
						1.32 m	

5000cd



AW
AS

10W LED 2700K-3000K / excl. 300mA LED Driver / 37V
10W LED 2700K-3000K / excl. 300mA LED Driver / 37V



High	1 m	2 m	3 m	4 m	5 m	illuminance	Diameter
60°	2377 lx	594 lx	264 lx	149 lx	95 lx	0.46 m	0.92 m
30°						1.39 m	1.85 m
						2.31 m	

2400cd



AW
AS

10W LED 2700K-3000K / excl. 300mA LED Driver / 37V
10W LED 2700K-3000K / excl. 300mA LED Driver / 37V



High	1 m	2 m	3 m	4 m	5 m	illuminance	Diameter
60°	1215 lx	304 lx	135 lx	76 lx	49 lx	0.65 m	1.30 m
30°						1.95 m	2.60 m
						3.25 m	

1250cd



AW
AS

10W LED 2700K-3000K / excl. 300mA LED Driver / 37V
10W LED 2700K-3000K / excl. 300mA LED Driver / 37V



High	1 m	2 m	3 m	4 m	5 m	illuminance	Diameter
60°	662 lx	166 lx	74 lx	41 lx	26 lx	1.15 m	2.31 m
30°						3.46 m	4.62 m
						5.77 m	

680cd



OSRAM LED Driver
Pout: 10W
Uout: 27 ~ 54VDC
Un: 100 ~ 240VAC
Iout: 290 ~ 420mA
AD0164



TCI LED Driver
Pout: 10W
Uout: 43VDC
Un: 100 ~ 240VAC
Iout: 290mA
AD0106