


LED BAW



NW: 0.40Kg

 111

 ∅ 110

 5 ~ 25mm

 P 100mm



R3B0363 AW
R3B0363 AS

Aluminum die-cast body and powder coating or oil painting finishing; By using the third generation of CITIZEN COB LED chip; good lighting effect, no lighting spot; available with different interchangeable beam angles.

Suitable for use in areas like hotels,villas,shopping malls and etc. This product is in compliance with CE and RoHS directives.

10W LED 2700K-3000K / excl. 240mA LED Driver / 37V
10W LED 2700K-3000K / excl. 240mA LED Driver / 37V



High	illuminance	Diameter
1 m	4976 lx	0.26 m
2 m	1244 lx	0.53 m
3 m	553 lx	0.79 m
4 m	311 lx	1.05 m
5 m	199 lx	1.32 m

60°
30°
6000cd



AW 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V
AS 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V



High	illuminance	Diameter
1 m	2377 lx	0.46 m
2 m	594 lx	0.92 m
3 m	264 lx	1.39 m
4 m	149 lx	1.85 m
5 m	95 lx	2.31 m

60°
30°
2400cd



AW 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V
AS 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V



High	illuminance	Diameter
1 m	1215 lx	0.65 m
2 m	304 lx	1.30 m
3 m	135 lx	1.95 m
4 m	76 lx	2.60 m
5 m	49 lx	3.25 m

60°
30°
1250cd



AW 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V
AS 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V



High	illuminance	Diameter
1 m	662 lx	1.15 m
2 m	166 lx	2.31 m
3 m	74 lx	3.46 m
4 m	41 lx	4.62 m
5 m	26 lx	5.77 m

60°
30°
830cd



OSRAM LED Driver
Pout: 10W
Uout: 27 ~ 54VDC
Un: 100 ~ 240VAC
Iout: 290 ~ 420mA
AD0164



TCI LED Driver
Pout: 10W
Uout: 43VDC
Un: 100 ~ 240VAC
Iout: 290mA
AD0106