


HIPLD-Flux



CE IP54
 NW: 0.26Kg

 88
 ∅ 102
 5 ~ 25mm
 P 98mm




R3B0178 AW

This product contains an aluminum die-cast front and a pure aluminum heat sink, completes with powder coating; By using the new generation of CITIZEN COB LED chip, this product creates extreme low heat and offers an excellent lumen performance; A range of PC reflectors are available with different beam angles, all completing with high reflecting vacuum plated finishing; Clip installation and adjustable; IP54

Suitable for use in areas like , hotel , fancy stores, supermarket and etc. This product is in compliance with CE and RoHS directives.

15W LED 2700K-3000K / excl. 360mA LED Driver / 37V


High	illuminance	Diameter
1 m	3416 lx	0.46 m
2 m	854 lx	0.92 m
3 m	380 lx	1.39 m
4 m	214 lx	1.85 m
5 m	137 lx	2.31 m



AW

15W LED 2700K-3000K / excl. 360mA LED Driver / 37V


High	illuminance	Diameter
1 m	1775 lx	0.65 m
2 m	444 lx	1.30 m
3 m	197 lx	1.95 m
4 m	111 lx	2.60 m
5 m	71 lx	3.25 m



AW

15W LED 2700K-3000K / excl. 360mA LED Driver / 37V

High	illuminance	Diameter
1 m	647 lx	1.15 m
2 m	162 lx	2.31 m
3 m	72 lx	3.46 m
4 m	40 lx	4.62 m
5 m	26 lx	5.77 m



OSRAM LED Driver
 Pout: 15W
 Uout: 27 ~ 54VDC
 Un: 220 ~ 240VAC
 Iout: 290 / 350 / 420mA
AD0164



TCI LED Driver
 Pout: 15W
 Uout: 43VDC
 Un: 100 ~ 240VAC
 Iout: 350mA
AD0104