


GW:



COB LED(CREE)

CE IP20
 NW:0.48 Kg

 ∅ 106
 109
 5 ~ 25mm
 100mm

R3B0509 AW
AS
AB

This product contains an aluminum die-cast front and a pure aluminum heat sink, completes with power coating or oil painting.

This product by using the high RA CREE light source the design of the low current, high voltage, reduces the heat coming from the light source when lit, improve the service life of the light source; High show better restore physical real color.

Lens with high light transmittance of PC material, to ensure the efficiency of light output, lens with multiple angles, cooperate to adjust the light angle of lamps, can satisfy the customer different angle and direction of lighting requirements.

This product use shrapnel installation, convenient disassembly, replacement and maintenance.


This product is in compliance with CE and RoHs directives.

20W LED 3000K / excl. 500mA LED Driver / 37V
 20W LED 3000K / excl. 500mA LED Driver / 37V
 20W LED 3000K / excl. 500mA LED Driver / 37V



1 m	5076 lx	0.42m
2 m	1269 lx	0.86 m
3 m	564 lx	1.30 m
4 m	317 lx	1.72 m
5 m	203 lx	2.15 m

High Illuminance Diameter




AW
AS
AB

20W LED 3000K / excl. 500mA LED Driver / 37V
 20W LED 3000K / excl. 500mA LED Driver / 37V
 20W LED 3000K / excl. 500mA LED Driver / 37V



1 m	3956 lx	0.55m
2 m	989 lx	1.11 m
3 m	439 lx	1.67 m
4 m	247 lx	2.23 m
5 m	158 lx	2.78 m

High Illuminance Diameter




AW
AS
AB

20W LED 3000K / excl. 500mA LED Driver / 37V
 20W LED 3000K / excl. 500mA LED Driver / 37V
 20W LED 3000K / excl. 500mA LED Driver / 37V



1 m	2168 lx	0.96 m
2 m	542 lx	1.92 m
3 m	240 lx	2.89 m
4 m	135 lx	3.85 m
5 m	86 lx	4.82 m

High Illuminance Diameter



Not dimmable
 Power : 30W
 Uout : 27~45VDC
 Un : 220~240VAC
 Lout : 500mA
AD0406



Dimmable
 Power : 20W
 Uout : 24~44VDC
 Un : 220~240VAC
 Lout : 500mA
AD0371