


Trim



GW: 8.28Kg

**CE IP20**  
 NW: 1.57Kg  
  
 +30° ~ -30° Tilt  
 169 x 165mm



COB LED(CITIZEN)

**R3B0339** AW

20W LED 2700K-3000K / excl. 480mA LED Driver / 37V

**R3B0339** AS

20W LED 2700K-3000K / excl. 480mA LED Driver / 37V



High	1 m	2 m	3 m	4 m	5 m	14900cd
60°	14766 lx	3692 lx	1461 lx	923 lx	591 lx	0.17 m
30°	0.17 m	0.35 m	0.50 m	0.67 m	0.85 m	
	High	illuminance	Diameter			



AW

20W LED 2700K-3000K / excl. 480mA LED Driver / 37V

AS

20W LED 2700K-3000K / excl. 480mA LED Driver / 37V



AW

20W LED 2700K-3000K / excl. 480mA LED Driver / 37V

AS

20W LED 2700K-3000K / excl. 480mA LED Driver / 37V



High	1 m	2 m	3 m	4 m	5 m	5100cd
60°	5076 lx	1269 lx	564 lx	317 lx	203 lx	0.42 m
30°	0.42 m	0.86 m	1.30 m	1.72 m	2.15 m	
	High	illuminance	Diameter			



AW

20W LED 2700K-3000K / excl. 480mA LED Driver / 37V

AS

20W LED 2700K-3000K / excl. 480mA LED Driver / 37V



High	1 m	2 m	3 m	4 m	5 m	2600cd
60°	2546 lx	637 lx	283 lx	159 lx	102 lx	0.57 m
30°	0.57 m	1.15 m	1.95 m	2.47 m	3.16 m	
	High	illuminance	Diameter			



AW

20W LED 2700K-3000K / excl. 480mA LED Driver / 37V

AS

20W LED 2700K-3000K / excl. 480mA LED Driver / 37V



High	1 m	2 m	3 m	4 m	5 m	1040cd
60°	1028 lx	257 lx	114 lx	64 lx	41 lx	1.15 m
30°	1.15 m	2.31 m	3.46 m	4.62 m	5.77 m	
	High	illuminance	Diameter			



**OSRAM** LED Driver  
 Pout: 20W  
 Uout: 27 ~ 54VDC  
 Uin: 220 ~ 240VAC  
 Iout: 500 / 600 / 700mA  
**AD0165**



**TCI** LED Driver  
 Pout: 20W  
 Uout: 45VDC  
 Uin: 110 ~ 240VAC  
 Iout: 500mA  
**AD0101**