


Trimless



GW: 11.72Kg

CE IP20
 NW: 1.62Kg

 +30° ~ -30° Tilt
 5 ~ 25mm
 164 x 164mm



R3B0123 AW
R3B0123 AS

15W LED 2700K-3000K / excl. 360mA LED Driver / 37V
 15W LED 2700K-3000K / excl. 360mA LED Driver / 37V


High	illumiance	Diameter
1 m	9059 lx	0.17 m
2 m	2265 lx	0.35 m
3 m	1007 lx	0.50 m
4 m	566 lx	0.67 m
5 m	362 lx	0.85 m



AW
 AS

15W LED 2700K-3000K / excl. 360mA LED Driver / 37V
 15W LED 2700K-3000K / excl. 360mA LED Driver / 37V

High	illumiance	Diameter
1 m	2771 lx	0.42 m
2 m	693 lx	0.86 m
3 m	308 lx	1.30 m
4 m	173 lx	1.72 m
5 m	111 lx	2.15 m



AW
 AS

15W LED 2700K-3000K / excl. 360mA LED Driver / 37V
 15W LED 2700K-3000K / excl. 360mA LED Driver / 37V

High	illumiance	Diameter
1 m	1780 lx	0.65 m
2 m	445 lx	1.30 m
3 m	198 lx	1.95 m
4 m	111 lx	2.60 m
5 m	71 lx	3.25 m



AW
 AS

15W LED 2700K-3000K / excl. 360mA LED Driver / 37V
 15W LED 2700K-3000K / excl. 360mA LED Driver / 37V

High	illumiance	Diameter
1 m	1780 lx	0.65 m
2 m	445 lx	1.30 m
3 m	198 lx	1.95 m
4 m	111 lx	2.60 m
5 m	71 lx	3.25 m



AW
 AS

15W LED 2700K-3000K / excl. 360mA LED Driver / 37V
 15W LED 2700K-3000K / excl. 360mA LED Driver / 37V

High	illumiance	Diameter
1 m	647 lx	1.15 m
2 m	162 lx	2.31 m
3 m	72 lx	3.46 m
4 m	40 lx	4.62 m
5 m	26 lx	5.77 m



OSRAM LED Driver
 Pout: 15W
 Uout: 27 ~ 54VDC
 Un: 220 ~ 240VAC
 Iout: 290 / 350 / 420mA
AD0164



TCI LED Driver
 Pout: 15W
 Uout: 43VDC
 Un: 100 ~ 240VAC
 Iout: 350mA
AD0104