

NW: 0.5Kg

↑ ▼ ♠ C€ IP20

30

8

5 ~ 25mm

47 106 x 106mm

10000

+30° ~ -30° Tilt







COB LED(CITIZEN)

This product contains an aluminum die-cast front and heat sink, completes with powder coating or oil painting finishing;

By using the new generation of CITIZEN COB LED chip, this product creates extreme low heat and offers an excellent lumen performance;

This product completes with high light transmittance PC lens, available with several different beam angles.

This product is with springs for recessed mounting.

It is suitable for hotels, department stores, various franchise stores, garment stores, superfine goods stores, art galleries, entertainment places, homes, etc.; This product is CE certified and all materials are in conformity with RoHS standard.

R3B0080 AW 7W LED 2700K-3000K / excl. 180mA LED Driver / 37V R3B0080 AS 7W LED 2700K-3000K / excl. 180mA LED Driver / 37V



| 153.   | 1 m  | 3112 lx     | 0.26 m   |
|--------|------|-------------|----------|
| 80° \  | 2 m  | 778 lx      | 0.53 m   |
|        | 3 m  | 346 lx      | 0.79 m   |
|        | 4 m  | 195 lx      | 1.05 m   |
| 3200cd | 5 m  | 124 lx      | 1.32 m   |
|        | High | illuminance | Diameter |



AW 7W LED 2700K-3000K / excl. 180mA LED Driver / 37V

7W LED 2700K-3000K / excl. 180mA LED Driver / 37V



| 1-1    | 1 m  | 1397 lx     | 0.46 m  |
|--------|------|-------------|---------|
| 60°    | 2 m  | 349 lx      | 0.92 m  |
|        | 3 m  | 155 lx      | 1.39 m  |
|        | 4 m  | 87 lx       | 1.85 m  |
| 1400cd | 5 m  | 56 lx       | 2.31 m  |
|        | High | illuminance | Diamete |

AS

AS



7W LED 2700K-3000K / excl. 180mA LED Driver / 37V AW AS

7W LED 2700K-3000K / excl. 180mA LED Driver / 37V



| 1030       | 1 01 | 995 lx      | 0.65 m  |
|------------|------|-------------|---------|
| 60°<br>30° | 2 m  | 249 lx      | 1.30 m  |
|            | 3 m  | 111 lx      | 1.95 m  |
|            | 4 m  | 62 lx       | 2.60 m  |
| 100000     | 5 m  | 40 lx       | 3.25 m  |
|            | High | illuminance | Diamete |



AW 7W LED 2700K-3000K / excl. 180mA LED Driver / 37V

7W LED 2700K-3000K / excl. 180mA LED Driver / 37V



| 101   | 100  | 274 lx     | 1.15 m     |
|-------|------|------------|------------|
| 30°   | 2 m  | 69 lx      | 2.31 m     |
|       | 3 m  | 30 lx      | 3.46 m     |
|       | 4 m  | 17 lx      | 4.62 m     |
| 280cs | 5 m  | 11 lx      | 5.77 m     |
| W     | High | illuminano | e Diameter |

