


LED BAW



Aluminum die-cast body and powder coating or oil painting finishing;
By using the third generation of CITIZEN COB LED chip; good lighting effect, no lighting spot; unique thermal ventilation system to create extreme low heat and offers an excellent lumen performance; available with different interchangeable beam angles.

With clip adjustment to have an easier installation.

Suitable for use in areas like hotels, villas, shopping malls and etc.
This product is in compliance with CE and RoHS directives.



COB LED(CITIZEN)

R3B0366 AW

15W LED 2700K-3000K / excl. 360mA LED Driver / 37V

R3B0366 AS

15W LED 2700K-3000K / excl. 360mA LED Driver / 37V



Height	1 m	2 m	3 m	4 m	5 m
Illuminance	9059 lx	2265 lx	1007 lx	566 lx	362 lx
Diameter	0.17 m	0.35 m	0.50 m	0.67 m	0.85 m



AW

15W LED 2700K-3000K / excl. 360mA LED Driver / 37V

AS

15W LED 2700K-3000K / excl. 360mA LED Driver / 37V



Height	1 m	2 m	3 m	4 m	5 m
Illuminance	2771 lx	693 lx	308 lx	173 lx	111 lx
Diameter	0.42 m	0.86 m	1.30 m	1.72 m	2.15 m



AW

15W LED 2700K-3000K / excl. 360mA LED Driver / 37V

AS

15W LED 2700K-3000K / excl. 360mA LED Driver / 37V



Height	1 m	2 m	3 m	4 m	5 m
Illuminance	1780 lx	445 lx	198 lx	111 lx	71 lx
Diameter	0.65 m	1.30 m	1.95 m	2.60 m	3.25 m



AW

15W LED 2700K-3000K / excl. 360mA LED Driver / 37V

AS

15W LED 2700K-3000K / excl. 360mA LED Driver / 37V



Height	1 m	2 m	3 m	4 m	5 m
Illuminance	647 lx	162 lx	72 lx	40 lx	26 lx
Diameter	1.15 m	2.31 m	3.46 m	4.62 m	5.77 m



OSRAM LED Driver
Pout: 15W
Uout: 27 ~ 54VDC
Un: 100 ~ 240VAC
Iout: 290 ~ 420mA
AD0164



TCI LED Driver
Pout: 15W
Uout: 43VDC
Un: 100 ~ 240VAC
Iout: 350mA
AD0104