



- T3A0046** XW
- T3A0046** AW
- T3A0046** YB

Pure Aluminum body and heatsink, powder coating finishing. By using the new generation of CITIZEN COB LED chip, this product creates extreme low heat and offers an excellent lumen performance. This product contains a combination of PMMA lens and aluminum reflector to achieve narrow beam performance. A range of reflectors are available with different beam angles, completing with high reflecting specular anodizing plated finishing. Adjustable direction, and mounting with 3 circuit track.

Suitable for use in areas like fancy stores, show rooms, gallery, museum etc. This product is in compliance with CE and RoHS directives.

- 30W LED 2700K-3000K / With 700mA LED Driver / 37V
- 30W LED 2700K-3000K / With 700mA LED Driver / 37V
- 30W LED 2700K-3000K / With 700mA LED Driver / 37V



High	illumiance	Diameter
1 m	15876 lx	0.17 m
2 m	3969 lx	0.35 m
3 m	1764 lx	0.50 m
4 m	992 lx	0.67 m
5 m	635 lx	0.85 m



- XW 30W LED 2700K-3000K / With 700mA LED Driver / 37V
- AW 30W LED 2700K-3000K / With 700mA LED Driver / 37V
- YB 30W LED 2700K-3000K / With 700mA LED Driver / 37V



- XW 30W LED 2700K-3000K / With 700mA LED Driver / 37V
- AW 30W LED 2700K-3000K / With 700mA LED Driver / 37V
- YB 30W LED 2700K-3000K / With 700mA LED Driver / 37V



High	illumiance	Diameter
1 m	7468 lx	0.42 m
2 m	1867 lx	0.86 m
3 m	830 lx	1.30 m
4 m	467 lx	1.72 m
5 m	299 lx	2.15 m



- XW 30W LED 2700K-3000K / With 700mA LED Driver / 37V
- AW 30W LED 2700K-3000K / With 700mA LED Driver / 37V
- YB 30W LED 2700K-3000K / With 700mA LED Driver / 37V



High	illumiance	Diameter
1 m	3097 lx	0.57 m
2 m	774 lx	1.15 m
3 m	344 lx	1.95 m
4 m	194 lx	2.47 m
5 m	124 lx	3.16 m

