

Focus-S




GW: 15.5Kg

NW: 0.27Kg

 0° ~ 30° Tilt

 COB LED(CITIZEN)

 P 83mm




COB LED(CITIZEN)

- R3B0253** AW 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V
- R3B0253** AS 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V
- R3B0253** WH 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V




High	illuminance	Diameter
1 m	4976 lx	0.26 m
2 m	1244 lx	0.53 m
3 m	553 lx	0.79 m
4 m	311 lx	1.05 m
5 m	199 lx	1.32 m



- AW 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V
- AS 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V
- WH 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V



High	illuminance	Diameter
1 m	2377 lx	0.46 m
2 m	594 lx	0.92 m
3 m	264 lx	1.39 m
4 m	149 lx	1.85 m
5 m	95 lx	2.31 m



- AW 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V
- AS 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V
- WH 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V




High	illuminance	Diameter
1 m	1215 lx	0.65 m
2 m	304 lx	1.30 m
3 m	135 lx	1.95 m
4 m	76 lx	2.60 m
5 m	49 lx	3.25 m



- AW 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V
- AS 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V
- WH 10W LED 2700K-3000K / excl. 240mA LED Driver / 37V



High	illuminance	Diameter
1 m	662 lx	1.15 m
2 m	166 lx	2.31 m
3 m	74 lx	3.46 m
4 m	41 lx	4.62 m
5 m	26 lx	5.77 m



OSRAM LED Driver
 Pout: 10W
 Uout: 27 ~ 54VDC
 Un: 220 ~ 240VAC
 Iout: 290 / 350 / 420mA
AD0164



TCI LED Driver
 Pout: 10W
 Uout: 43VDC
 Un: 100 ~ 240VAC
 Iout: 290mA
AD0106